

Ultima Smart Toric

Customized Design, Predictable Refractive Outcome

Hydrophilic



Innovative Intraocular Lens
Customized Optic Size & Overall Length
for Each Patients.



EYEOL U.K. LIMITED

Treating Astigmatism was never so easy


- No Axis marking
- No Rhexis Marking
- No Alignment
- No Lens Rotation
- ELP Optimized Design
- Anti - Rotation haptic Pads



UST Ensures 100% Predictable Refractive Outcome

Specification:	Model	Ultima Smart Toric
	Material	Hydrophilic Acrylic (Yellow Tinted)
	IOL Powers	-10.00 D to +40.00 D (In 0.5 D Steps)
	Cylinder Power	+0.50 D to 10.00 D (in 0.5 D Steps)
		Customized Cylinder Range 11.00 D to 20.00 D (in 0.5 D Steps)
	Optic Diameter	6.0 mm (Customized Range 5 mm to 6.5 mm)
	Overall Length	11.00 mm (Customized Range 11 mm to 14 mm (0.25 Steps))
	Optic Type	Toric Aspheric Optic
	Haptic Angulation	0 Degrees (Planner)
	Haptic Configuration	Modified Plate haptic
	Abbe Number	>58
	Refractive Index	1.465
	A-Constant	118.4 (SRK-T, US Biometry)*
		118.28 (SRK-T, Optical Biometry)*
	Online Calculator	www.toric.caregroupindia.com

*The values are of estimates only. It is recommended that the surgeon derive his / her own values based on data of the eye to be operated upon & characteristic of IOL.



EYEOL U.K. LIMITED

8 Apex Business Centre,
Boscombe Road, Dunstable,
Bedfordshire, LU5 4SB, U.K.
Fax: +44 1582 607009
Phone: +44 (0) 1582 477002
Email: info@eyeol.co.uk
Web: www.eyeol.co.uk